

## 19" 1U Horizontal Type Aluminium Frame PDU

### 6 x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1000	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 x German Type (DIN 49440) Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm

### 6 x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1001	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 x French Type Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm

### 4 x UK Type (BS 1363) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1002	1 Phase 250 VAC Input IP20, 13 A, 2.8 Kw , 4 x UK Type (BS 1363) Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with 13A fused BS 1363 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm

### 6 x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1003	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 x IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm
M-PDU-1004	1 Phase 250 VAC Input IP20, 10 A, 2.2 kW , 6 x IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,0 mm <sup>2</sup> black cord with IEC-C14 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm
M-PDU-1005	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 x IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC-C20 Plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm



# Metered PDU

## 19" 1U Horizontal Type Aluminium Frame PDU

### 8 x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1006	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 8 x IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm
M-PDU-1007	1 Phase 250 VAC Input IP20, 10 A, 2.2 kW , 8 x IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,0 mm <sup>2</sup> black cord with IEC-C14 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm
M-PDU-1008	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 8 x IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC-C20 Plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm

### 4 x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1009	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 4 x C19 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC-C20 Plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm
M-PDU-1010	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 4 x C19 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm

### 4 x IEC320 C13 Socket + 2 x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-1011	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 4 x IEC320 C13 Socket + 2 x C19 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm
M-PDU-1012	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 4 x IEC320 C13 Socket + 2 x C19 Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC-C20 Plug	Digital Ammeter With Overload Alarm	482 X 44 X 44 mm



## 19" 2U Horizontal Type Aluminium Frame PDU

### 9 x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-2000	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 9 x German Type (DIN 49440) Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 88 mm
M-PDU-2001	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 9 x German Type (DIN 49440) Socket, On/off switch With Thermal Protection, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	On/off switch With Thermal Protection, Digital Ammeter With Overload Alarm	482 X 44 X 88 mm
M-PDU-2002	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 9 x German Type (DIN 49440) Socket, On/off switch With Thermal Protection, Surge Protection, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	On/off switch With Thermal Protection, Surge Protection, Digital Ammeter With Overload Alarm	482 X 44 X 88 mm

### 9 x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-2003	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 9 x French Type Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	Digital Ammeter With Overload Alarm	482 X 44 X 88 mm
M-PDU-2004	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 9 x French Type Socket, On/off switch With Thermal Protection, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	On/off switch With Thermal Protection, Digital Ammeter With Overload Alarm	482 X 44 X 88 mm
M-PDU-2005	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 9 x French Type Socket, On/off switch With Thermal Protection, Surge Protection, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with DIN 49441 plug	On/off switch With Thermal Protection, Surge Protection, Digital Ammeter With Overload Alarm	482 X 44 X 88 mm

### 9 x UK Type (BS 1363) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-2006	1 Phase 250 VAC Input IP20, 13 A , 2.8 Kw , 9 x UK Type (BS 1363) Socket, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with 13A fused BS 1363 plug	Digital Ammeter With Overload Alarm	482 X 44 X 88 mm
M-PDU-2007	1 Phase 250 VAC Input IP20, 13 A , 2.8 Kw , 9 x UK Type (BS 1363) Socket, On/off switch With Thermal Protection, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with 13A fused BS 1363 plug	On/off switch With Thermal Protection, Digital Ammeter With Overload Alarm	482 X 44 X 88 mm
M-PDU-2008	1 Phase 250 VAC Input IP20, 13 A , 2.8 Kw , 9 x UK Type (BS 1363) Socket, On/off switch With Thermal Protection, Surge Protection, Digital Ammeter With Overload Alarm, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with 13A fused BS 1363 plug	On/off switch With Thermal Protection, Surge Protection, Digital Ammeter With Overload Alarm	482 X 44 X 88 mm



# Metered PDU

## 26U Vertical Type Aluminium Frame PDU

### (6 + 6) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0001	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 + 6 x German Type (DIN 49440) Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1156 X 44 X 44 mm

### (6 + 6) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0002	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 + 6 x French Type Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1156 X 44 X 44 mm

### (6 + 6) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0003	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 + 6 X IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1156 X 44 X 44 mm

### (4 + 4) x IEC320 C13 Socket+ (2+2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0004	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, (4 + 4) x IEC320 C13 Socket + (2+2) x C19 Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1156 X 44 X 44 mm



## 32U Vertical Type Aluminium Frame PDU

### (6 + 6) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0005	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 + 6 x German Type (DIN 49440) Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1422 X 44 X 44 mm

### (6 + 6) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0006	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 + 6 x French Type Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1422 X 44 X 44 mm

### (6 + 6) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0007	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, 6 + 6 X IEC320 C13 Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1422 X 44 X 44 mm

### (4 + 4) x IEC320 C13 Socket + (2+2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0008	1 Phase 250 VAC Input IP20, 16 A, 3.5 kW, (4 + 4) x IEC320 C13 Socket + (2+2) x C19 Socket, Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker, 2m H05VV-F 3G1,5 mm <sup>2</sup> black cord with IEC309-1P 16A plug	Digital Ammeter With Overload Alarm, 2X16A Circuit Breaker	1422 X 44 X 44 mm



# Metered PDU

## 42U Vertical Type Aluminium Frame PDU

### (6 + 6 + 6) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0009	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (6 + 6 + 6) x German Type (DIN 49440) Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	1867 X 44 X 44 mm

### (6 + 6 + 6) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0010	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (6 + 6 + 6) x French Type Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	1867 X 44 X 44 mm

### (6 + 6 + 6) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0011	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (6 + 6 + 6) X IEC320 C13 Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	1867 X 44 X 44 mm

### (4+4+4) x IEC320 C13 Socket + (2+2+2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0012	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (4+4+4) x IEC320 C13 Socket + (2+2+2) x C19 Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	1867 X 44 X 44 mm



## 45U Vertical Type Aluminium Frame PDU

### (6 + 6 + 6) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0013	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (6 + 6 + 6) x German Type (DIN 49440) Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2000 X 44 X 44 mm

### (6 + 6 + 6) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0014	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (6 + 6 + 6) x French Type Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2000 X 44 X 44 mm

### (6 + 6 + 6) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0015	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , (6 + 6 + 6) X IEC320 C13 Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2000 X 44 X 44 mm

### (6 + 6) x IEC320 C13 Socket + 6 x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0016	3 Phase 400 VAC Input IP 20 , 16 A, 10.5 kW , 6 + 6 X IEC320 C13 Socket + 6 x C19 Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2000 X 44 X 44 mm



# Metered PDU

## 47U Vertical Type Aluminium Frame PDU

### (6 + 6 + 6) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0017	3 Phase 400 VAC Input IP 20, 16 A, 10.5 kW , (6 + 6 + 6) x German Type (DIN 49440) Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16 Circuit Breaker	2090 X 44 X 44 mm

### (6 + 6 + 6) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0018	3 Phase 400 VAC Input IP 20, 16 A, 10.5 kW , (6 + 6 + 6) x French Type Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2090 X 44 X 44 mm

### (6 + 6 + 6) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0019	3 Phase 400 VAC Input IP 20, 16 A, 10.5 kW , (6 + 6 + 6) X IEC320 C13 Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2090 X 44 X 44 mm

### (4 + 4 + 4) x IEC320 C13 Socket + (2 + 2 + 2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0020	3 Phase 400 VAC Input IP 20, 16 A, 10.5 kW , (4 + 4 + 4) x IEC320 C13 Socket + (2 + 2 + 2) x C19 Socket, 3X Digital Ammeter With Overload Alarm, 3X16A Circuit Breaker, 2m 5x2,5 mm <sup>2</sup> black cord with IEC309-3P 16A plug	3XDigital Ammeter With Overload Alarm, 3X16A Circuit Breaker	2090 X 44 X 44 mm





## 42U Vertical Type Aluminium Frame PDU

### (8 + 8 + 8) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0021	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) x German Type (DIN 49440) Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	1867 X 44 X 44 mm

### (8 + 8 + 8) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0022	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) x French Type Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	1867 X 44 X 44 mm

### (8 + 8 + 8) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0023	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) X IEC320 C13 Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	1867 X 44 X 44 mm

### (6 + 6 + 6) x IEC320 C13 Socket + (2 + 2 + 2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0024	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (6 + 6 + 6) X IEC320 C13 Socket + (2+2+2) x C19 Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	1867 X 44 X 44 mm



# Metered PDU

## 45U Vertical Type Aluminium Frame PDU

### (8 + 8 + 8) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0025	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) x German Type (DIN 49440) Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2000 X 44 X 44 mm

### (8 + 8 + 8) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0026	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) x French Type Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2000 X 44 X 44 mm

### (8 + 8 + 8) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0027	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) X IEC320 C13 Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2000 X 44 X 44 mm

### (6 + 6 + 6) x IEC320 C13 Socket+ (2+2+2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0028	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (6 + 6 + 6) X IEC320 C13 Socket + (2+2+2) x C19 Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2000 X 44 X 44 mm



## 47U Vertical Type Aluminium Frame PDU

### (8 + 8 + 8) x German Type (DIN 49440) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0029	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) x German Type (DIN 49440) Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2090 X 44 X 44 mm

### (8 + 8 + 8) x French Type (NF C 61314) Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0030	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) x French Type Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2090 X 44 X 44 mm

### (8 + 8 + 8) x IEC320 C13 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0031	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (8 + 8 + 8) X IEC320 C13 Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2090 X 44 X 44 mm

### (6 + 6 + 6) x IEC320 C13 Socket + (2+2+2) x IEC320 C19 Socket

PRODUCT CODE	PRODUCT DESCRIPTION	OPTIONS	DIMENSION
M-PDU-0032	3 Phase 400 VAC Input IP 20, 32 A, 21 kW , (6 + 6 + 6) X IEC320 C13 Socket + (2+2+2) x C19 Socket, 3X Digital Ammeter With Overload Alarm, 3X32A Circuit Breaker, 2m 5x4 mm <sup>2</sup> black cord with IEC309-3P 32A plug	3XDigital Ammeter With Overload Alarm, 3X32A Circuit Breaker	2090 X 44 X 44 mm

